

Display Size	6.4"	8.4"	10.4"	12.1"	15"	17"	19"
Operating Temp	-20C to +65C	-20C to +65C	-20C to +65C	-20C to +65C	-20C to +65C	-20C to +65C	-20C to +65C
Storage Temp	-20C to +70C	-20C to +70C	-20C to +70C	-20C to +70C	-20C to +70C	-20C to +70C	-20C to +70C
Environmental Humidity	90%RH	90%RH	90%RH	90%RH	90%RH	90%RH	90% RH
OSD	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Backlight	LED	LED	LED	LED	LED	LED	LED
Dimming	Max Brightness to Black	Max Brightness to Black	Max Brightness to Black	Max Brightness to Black	Max Brightness to Black	Max Brightness to Black	Max Brightness to Black
Outside Dimensions (W x H x D)	240mm x 168mm x 51mm	262mm x 192mm x 51mm	324mm x 236mm x 60mm	334mm x 272.5mm x 50.5mm	418mm x 306mm x 60mm	428mm x 352.5mm x 66.5mm	476mm x 382mm x 65mm
Mechanical Drawing	01-6421-260-2	01-8421-261-2	01-1021-262-2	01-1221-263-2	01-1521-264-2	01-1721-265-2	01-1921-266-2

6-Wire Resistive Touch Screen	Controller + USB cable
Part Number	N/A
Optical Clarity	94% light transmission
Surface	6H Hard Coat
Durability	Over one million touches
Linearity	Better than 1.5%
Altitude	15,000 ft
Operating Temperature	-20C to +65C
Communication Interface	USB
Isolation	Greater than 20M ohm at +25C
Operating System	Windows 98/2000XP/Linus/CE

Notes

1. Email to info@insyncperipherals.com for touch screen software driver.
2. Other video input signals are available.